



Installation Method



Monolithic

Interface European Manufacturing BV reserve the right to change or modify specifications.

Collection Barricade **Product** Barricade Two **Colour** 4200003 Brown

Product Specifications

Product Number	4200
Product Construction	Tufted Plain Textured Loop Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex®
Size – Packaging	50 x 50 cm – 4 m² Box
Pile Yarn Weight	726 g/m² ± 5%
Total Weight	4305 g/m² ± 5%
Pile Height	3.6 mm +15% / - 10%
Total Thickness	6.9 mm ± 0.5 mm
Gauge – Ends per 10 cm	5/32 - 25.2
Tufts per m²	100,800/m² ±5%

Performance Specifications

Wear Classification	EN 1307 32 General Contract	
Castor Chair Rating	≥2.0 (EN 985) Occasional Use (EN ISO 9239-1) Euroclass Cf1-s1 (EN 13501-1)	
Flammability	Bfl-s1 on request	
Light Fastness	≥7 (ISO 105-B02)	
Light Reflectance Value (LRV)	LRV – L value 22.2	LRV – Y value 3.6
Dimensional Stability	≤0.2% (ISO 2551/EN 986)	

Environmental Specifications

Total Recycled Content	74.54%
Pre-Consumer (Total)	66.11%
Post-Consumer (Total)	8.43%
Yarn Recycled Content	100%
Pre-Consumer (Yarn)	50%
Post-Consumer (Yarn)	50%
Indoor Air Quality	GUT Prodis ID A0FEC6D0 French A+ Danish Indoor Climate GLP 9819 GUI Standard
Potential Green Building Contribution	
BREEAM (UK/International)	View potential BREEAM contribution
LEED (US/International)	View Potential Leed Contribution
HQE (France)	View Potential HQE Contribution
DGNB (Germany)	View Potential DGNB Contribution
Environmental Product Declaration	EPD-IFF-20120019-CBD1-EN

Carbon Footprint

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	7.78 kg CO ₂ eq./m ²
Delivery and Installation	0.7 kg CO ₂ eq./m ²
Use (10 Years)	2.92 kg CO ₂ eq./m ²
End of Life (Waste to Energy)	8.57 kg CO ₂ eq./m ²
Total (10 Years Lifetime)	19.97 kg CO ₂ eq./m ²
Carbon Neutral Cool Carpet®	Standard

Installation Impacts

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below: Monolithic – 3-4% For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

End of Life Options

ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.

Technical Information

Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	7 years
Manufacturing Location	ISO 9001 & 14001 Certified Facilities in Europe

Performance Qualifications



Certifications

